\bigcirc

WARNING

۲

The power light turns red to indicate low battery power and turns off when the battery level is less than 10 %. Remember to charge the device on time to avoid any problem.

Store the wireless microphone in a dry and ventilated place to avoid humidity.

Do not open the device yourself. For any service or repair please contact your local distributor or a qualified specialist.

We reserve the right to update specifications and instructions without further notice.

Stagg







EMD Music - 07/2019

۲

SUW 12H-BE BEIGE WIRELESS HEADSET MICROPHONE SET

Please read the instructions carefully before use

UserManSUW12H-BE.indd 1

 (\bullet)



PRODUCT FEATURES

Wireless 2.4 GHz headset condenser microphone transmitter and receiver Couple automatically, easy to operate

Up to 4 identical systems can work together

Both transmitter and receiver work on rechargeable lithium battery Work together with battery-powered speakers for a versatile solution Up to 6 hours using time

Suitable for many different situations, such as presentations, educational events and singing performances. Could be used as a computer microphone and for video sound recording

PACKAGE CONTENT

۲

•

Transmitter	1
Receiver	1
Beige headset with boom microphone	1
6.35 mm audio adapter plug	1
Double charger cord	1
User manual	1

INSTRUCTIONS

- 1. Connect the receiver to the MIC input of an amplifier, speaker or other audio equipment. Use the 6.35 mm audio adapter plug if needed.
- 2. Turn on the receiver using the power switch. The power light will blink.



 Turn on the transmitter using the power switch. The power light will blink. The transmitter and receiver will match automatically. Once matched, the power lights stay on.



4. Adjust the volume to the desired level thanks to the volume buttons.



5. Place the microphone. The system is ready to use.

TECHNICAL PARAMETERS

()

Frequency range: 2.4 GHZ Frequency response: 20 Hz - 20 KHz (+- 3 dB) Output impedance: \leq 2200 ohms Pairing method: Automatic Microphone type: Condenser Microphone diameter: 6 x 2.7 mm (0.2 x 0.1") Microphone sensitivity: - 45 dB (+- 2dB) Signal to noise ration: > 63 dB Power supply: Rechargeable lithium battery Power consumption: < 70 mA at 0 dBm Operating voltage: 2.0 – 10 V DC Operational distance: 25 metres (82 feet) Operational time: Up to 6 hours