Product Bulletin Sub10 MK2





Description:

The Sub10 MK 2 is a powerful subwoofer designed to extend the low frequency capabilties of any near- or midfield monitoring system. The Sub10 MK 2 houses an excellent 10" woofer with a large 50 mm voice coil, and is driven by a 200 W Ice Power amp. This amp stays cool as it uses PWM = pulse widfth modulation in the amp and the power supply section, thus arriving at a > 80% over all efficiency. It can handle its maximum power without danger for the electronics or the driver.

The now available MK 2 version works with a new downfiring bass reflex tube, that due to ist shape and size avoids "breathing" noise from the tube with much more effect.

For larger rooms or higher levels it is possible to chain as many Sub10 MK 2´s as necessary. All in- and outputs have both XLR and RCA(Cinch) connectors.

The Sub10 MK 2 is an ideal match for ADAM monitors such as the P series or the S1A through S3A studio monitors.



Technical data	Sub 10 MK 2
Driver	260 mm (10")
Free air resonance	26 Hz
Voice coil ø	50 mm (2")
Cone material	coated paper
Built in amps:	200 W/300 W
Frequ. response ±3dB	25 Hz - var. 50 - 150 Hz
THD >80Hz	≤0,8 %
SPL max in 1 m	≥ 119 dB SPL
Crossover frequ. (telecommander)	50 Hz - 150 Hz
In- and outputs	balanced XLR + unbalanced RCA
Input impedance	10 kΩ
Weight	21 kg (46 lbs)
Magnetical shielding	no
Width x Height x Depth	30 x 55 x 40 cm (11.8" x 21.6" x 15.7")
Warranty	2 years

ADAM Audio GmbH

Lobeckstr. 36 | 10969 Berlin-Germany phone: +45 30-863 00 97-0 fax: +45 30-863 00 97-7 email: info@adam-audio.com web: www.adam-audio.com **ADAM USA**

3717 E. Thousand Oaks Blvd.

Suite 215 | Westlake Village | CA, 91362
phone: +1 805-413 11 33
fax: +1-805-413 11 34
email: usa@adam-audio.com

ADAM Audio Asia Pte. Ltd.

51, Changi Business Park Central 2 #08-03, The Signature | Singapore 486066 phone: +65-67 25 81 81 fax: +65-67 25 81 82

fax: +65-67 25 81 82 email: asia@adam-audio.com