Optional Brakets (HS-I only)

- * Mounting points on 4 surfaces: HS8I / HS7I: 2 x M8 (120 mm pitch), HS5I: 2 x M5 (60 mm pitch). Screws for installing brackets are included with HS8I/HS7I/HS5I.
- * Do not install the speaker transversely.
- * When choosing the installation location such as wall and ceiling and mounting hardware (bolts, nuts), make sure all are strong enough to support the weight of the speaker and braket.

Wall mount



Speaker	Bracket			
	Model	Maximum tilt angle	Net weight	Color
HS8I / HS8I (White)	BWS251-300	30°	4.4kg; 9.7lbs	Black
	BWS251-400	45°	5.2kg; 11.5lbs	Black
	BWS50-260	0°	1.4kg; 3.1lbs	Black
	BWS50-190	Not compatible		
HS7I / HS7I (White)	BWS251-300	35°	4.4kg; 9.7lbs	Black
	BWS251-400	45°	5.2kg; 11.5lbs	Black
	BWS50-260	0°	1.4kg; 3.1lbs	Black
	BWS50-190	Not compatible		
HS5I / HS5I (White)	BWS20-190	0°	0.85kg; 1.9lbs	Black
	BWS20-120	Not compatible		

Ceiling mount



Speaker	Bracket			
	Model	Maximum tilt angle	Net weight	Color
HS8I / HS8I (White)	BCS251	45°	2.3kg; 5.1lbs	Black
	BWS50-260	30°	1.4kg; 3.1lbs	Black
	BWS50-190		1.2kg; 2.6lbs	Black
HS7I / HS7I (White)	BCS251	45°	2.3kg; 5.1lbs	Black
	BWS50-260	30°	1.4kg; 3.1lbs	Black
	BWS50-190		1.2kg; 2.6lbs	Black
HS5I / HS5I (White)	BCS20-210	20°	1.0kg; 2.2lbs	Black

BCS20-150	0.9kg; 2lbs	Black
BWS20-190	0.85kg; 1.9lbs	Black
BWS20-120	0.6kg; 1.3lbs	Black

Baton mount



Speaker	Bracket		
Speaker	Model	Net weight	Color
HS8I / HS8I (White) HS7I / HS7I (White)	DDC2E1	2 2lzg, E 1lbg	Dlack
HS7I / HS7I (White)	DD3231	2.5kg, 5.110s	DIACK
HS5I / HS5I (White)		Not compatib	le